

WSF-00177 DCS Receive Bandpass Filter

◆ Features:

- Excellent Selectivity
 >60 dB @ 1900 MHz & >50dB
 @2000 MHz (Bandedges + 20 MHz)
- Low Insertion Loss
- Small Size



◆ Specifications:

Passbands:	1710 to 1785 MHz	Operating Humidity:	0 to 90%, Relative, non-condensing
Passband Insertion Loss:	1.5 dB max.	Dimensions: (excluding connectors):	5.45"L x 2.67"W x 1.67"H (355.6mm x 152.4mm x 55.9mm)
Passband Return Loss:	15 dB min.	Connectors:	SMA-F
Rejection			
DC to 1615MHz:	50 dB min.		
1805 to 2700MHz:	50 dB min.		
Operating Temperature:	0 to +50°C		
Storage Temperature:	-40° to +85°C		

◆ Applications:

- Picocell, Microcell and Macrocell Base Station Installations
- Handset or Equipment Test Systems

Filtering Solutions for Your Global Market

USA

Phone: 410-749-2424
FAX: 410-749-5725
Email: sales@klmicrowave.com

EUROPE

Phone: +44-(0)-1908-547920
FAX: +44-(0)-1908-695284
Email: sales@kleurope.com

Order On-Line @ www.klmicrowave.com

